



PDS No. 6781xx-CF1/ 6781xx-CF2	PRODUCT DATA SHEET				Page 1 of 2
Revision 02	CELLdisc, External Filter, Closed Filling Cap, TC, Triple Packed, Sterile				
	Greiner Item-No. 6781xx-CF1 / 6781xx-CF2				
Valid for Item-No.:	678101-CF1 (sterile)	678104-CF1 (sterile)	678108-CF1 (sterile)	678112-CF1 (sterile)	678116-CF1 (sterile)
	678124-CF1 (sterile)	678140-CF1 (sterile)	678104-CF2 (sterile)	678108-CF2 (sterile)	678112-CF2 (sterile)
	678116-CF2 (sterile)	678124-CF2 (sterile)	678140-CF2 (sterile)		

1.	Description / Specification																	
1.1	Description	<p>Celldisc, multilayer device, from 250 cm² to 10.000 cm², physical surface treatment, ventilation through central gas support channel, gas inlet and outlet equipped with external filters, red screw cap, either with single tubing (-CF1; filling tube only) or double tubing (-CF2; filling tube + dip-in tube for liquid removal), triple packed, sterile</p> <p><i>678101-CF1</i>: 1 layer, 250 cm², screw cap with 1 tube <i>678104-CF1</i>: 4 layers, 1.000 cm², screw cap with 1 tube <i>678108-CF1</i>: 8 layers, 2.000 cm², screw cap with 1 tube <i>678112-CF1</i>: 12 layers, 3.000 cm², screw cap with 1 tube <i>678116-CF1</i>: 16 layers, 4.000 cm², screw cap with 1 tube <i>678124-CF1</i>: 24 layers, 6.000 cm², screw cap with 1 tube <i>678140-CF1</i>: 40 layers, 10.000 cm², screw cap with 1 tube <i>678104-CF2</i>: 4 layers, 1.000 cm², screw cap with 2 tubes <i>678108-CF2</i>: 8 layers, 2.000 cm², screw cap with 2 tubes <i>678112-CF2</i>: 12 layers, 3.000 cm², screw cap with 2 tubes <i>678116-CF2</i>: 16 layers, 4.000 cm², screw cap with 2 tubes <i>678124-CF2</i>: 24 layers, 6.000 cm², screw cap with 2 tubes <i>678140-CF2</i>: 40 layers, 10.000 cm², screw cap with 2 tubes</p>																
1.2	Dimensions	<p>See Customer Drawings</p> <p><u>External Filter</u>: pore size of filter membrane: 0.2 µm</p>																
1.3	Volume / Growth area	<table border="0"> <tr> <td><u>Working volume</u>:</td> <td><u>Growth area</u>:</td> </tr> <tr> <td><i>678101-CF1</i>: 15-50 ml</td> <td><i>678101-CF1, -CF2</i>: 250 cm²</td> </tr> <tr> <td><i>678104-CF1, -CF2</i>: 60-200 ml</td> <td><i>678104-CF1, -CF2</i>: 1.000 cm²</td> </tr> <tr> <td><i>678108-CF1, -CF2</i>: 120-400 ml</td> <td><i>678108-CF1, -CF2</i>: 2.000 cm²</td> </tr> <tr> <td><i>678112-CF1, -CF2</i>: 180-600 ml</td> <td><i>678112-CF1, -CF2</i>: 3.000 cm²</td> </tr> <tr> <td><i>678116-CF1, -CF2</i>: 240-1000 ml</td> <td><i>678116-CF1, -CF2</i>: 4.000 cm²</td> </tr> <tr> <td><i>678124-CF1, -CF2</i>: 360-1200 ml</td> <td><i>678124-CF1, -CF2</i>: 6.000 cm²</td> </tr> <tr> <td><i>678140-CF1, -CF2</i>: 600-2000 ml</td> <td><i>678140-CF1, -CF2</i>: 10.000 cm²</td> </tr> </table>	<u>Working volume</u> :	<u>Growth area</u> :	<i>678101-CF1</i> : 15-50 ml	<i>678101-CF1, -CF2</i> : 250 cm ²	<i>678104-CF1, -CF2</i> : 60-200 ml	<i>678104-CF1, -CF2</i> : 1.000 cm ²	<i>678108-CF1, -CF2</i> : 120-400 ml	<i>678108-CF1, -CF2</i> : 2.000 cm ²	<i>678112-CF1, -CF2</i> : 180-600 ml	<i>678112-CF1, -CF2</i> : 3.000 cm ²	<i>678116-CF1, -CF2</i> : 240-1000 ml	<i>678116-CF1, -CF2</i> : 4.000 cm ²	<i>678124-CF1, -CF2</i> : 360-1200 ml	<i>678124-CF1, -CF2</i> : 6.000 cm ²	<i>678140-CF1, -CF2</i> : 600-2000 ml	<i>678140-CF1, -CF2</i> : 10.000 cm ²
<u>Working volume</u> :	<u>Growth area</u> :																	
<i>678101-CF1</i> : 15-50 ml	<i>678101-CF1, -CF2</i> : 250 cm ²																	
<i>678104-CF1, -CF2</i> : 60-200 ml	<i>678104-CF1, -CF2</i> : 1.000 cm ²																	
<i>678108-CF1, -CF2</i> : 120-400 ml	<i>678108-CF1, -CF2</i> : 2.000 cm ²																	
<i>678112-CF1, -CF2</i> : 180-600 ml	<i>678112-CF1, -CF2</i> : 3.000 cm ²																	
<i>678116-CF1, -CF2</i> : 240-1000 ml	<i>678116-CF1, -CF2</i> : 4.000 cm ²																	
<i>678124-CF1, -CF2</i> : 360-1200 ml	<i>678124-CF1, -CF2</i> : 6.000 cm ²																	
<i>678140-CF1, -CF2</i> : 600-2000 ml	<i>678140-CF1, -CF2</i> : 10.000 cm ²																	
1.4	Material / Resin	<p><u>Disc</u>: PS (Polystyrene), free of heavy metal <u>Cap</u>: HDPE (High Density Polyethylene), free of heavy metal <u>External Filter</u>: Membrane: PES (Polyethersulfone) Support Fleece: Polyester Housing: PP (Polypropylene)</p> <p><u>Tube</u>: Silicone</p>																
1.5	Colour	<p><u>Disc</u>: clear <u>Cap</u>: red <u>External Filter</u>: nature <u>Tube</u>: nature</p>																
1.6	Sterilization	SAL 10 ⁻⁶																
1.7	Quality Control	<p>- <u>Raw Material-Control</u>: physical testing - <u>Product-Control</u>: testing of attributive and variable characteristics in accordance with the valid specification</p>																
1.8	Intended Use	General laboratory product for cell culture to be used by qualified personnel in a laboratory environment.																
1.9	Other Information	For single use only																

Data Sheet subject to change without notice!

Prior Issue	Drawn	Approved	Released	CONFIDENTIAL: Information contained in this document or drawing is confidential and proprietary to Greiner Bio-One GmbH. This document may not be reproduced for any reason without written permission from Greiner Bio-One GmbH. All rights of design, invention, and copyright are reserved.
Revision 01	Date 14 September 2023	Date 14 September 2023	Date 14 September 2023	
Date 25.02.2021	Name S. Kaelberer	Name Jens Gaiser	Name Dr. C.-K. Chai	

DISCLAIMER: The description of a certain product can only be considered as a guidance, because its performance ultimately depends on what the product is used for. Very often performance studies are indispensable.

PDS No. 6781xx-CF1/ 6781xx-CF2	PRODUCT DATA SHEET				Page 2 of 2
Revision 02	CELLdisc, External Filter, Closed Filling Cap, TC, Triple Packed, Sterile				
	Greiner Item-No. 6781xx-CF1 / 6781xx-CF2				
Valid for Item-No.:	678101-CF1 (sterile)	678104-CF1 (sterile)	678108-CF1 (sterile)	678112-CF1 (sterile)	678116-CF1 (sterile)
	678124-CF1 (sterile)	678140-CF1 (sterile)	678104-CF2 (sterile)	678108-CF2 (sterile)	678112-CF2 (sterile)
	678116-CF2 (sterile)	678124-CF2 (sterile)	678140-CF2 (sterile)		

2.	Features	
2.1	Basic features	Free of detectable DNase/RNase, human DNA and pyrogens. Contents non-cytotoxic
2.2	Temperature range	For application: 4°C to +37 °C
2.3	Autoclavability	No
2.4	Centrifugation, max. RCF	-
2.5	Chemical Resistance	See homepage: https://www.gbo.com/en_INT/know-how-services/download-center.html
2.6	Shelf life	4 years
2.7	Other Information	USP Class VI tested

3.	Packaging	678101-CF1	678104-CF1, -CF2	678108-CF1, -CF2	678112-CF1, -CF2, -116-CF1, -CF2, -124-CF1, -CF2	678140-CF1, -CF2
3.1	Pieces/Bag (triple packed)	1	1	1	1	1
3.2	Pieces/Box	4	3	2	2	1
3.3	Lot-No.	E YY MM XXX (manufacturing facility, year, month, consecutive SAP-No.)				
3.4	Other Information	Certificate of Quality to download				

4.	Other Information
4.1	Research use only. Not for diagnostics.

Data Sheet subject to change without notice!

Prior Issue	Drawn	Approved	Released	CONFIDENTIAL: Information contained in this document or drawing is confidential and proprietary to Greiner Bio-One GmbH. This document may not be reproduced for any reason without written permission from Greiner Bio-One GmbH. All rights of design, invention, and copyright are reserved.
Revision 01	Date 14 September 2023	Date 14 September 2023	Date 14 September 2023	
Date 25.02.2021	Name S. Kaelberer	Name Jens Gaiser	Name Dr. C.-K. Chai	

DISCLAIMER: The description of a certain product can only be considered as a guidance, because its performance ultimately depends on what the product is used for. Very often performance studies are indispensable.