1.	**Description / Specification**	
1.1	Description	384 well SCREENSTAR Microplate, Cycloolefin Frame, Cycloolefin Film Bottom, F-Bottom, Rounded Square Well Design, No Alphanumeric Well Coding, Physical Surface Treatment, with Lid (ultra-low profile), Sterile
1.2	Dimensions	See Customer Drawing
1.3	Volume per well	Total volume: 103.7 µl (mathematical calculated) Working volume: 10 – 95 µl Growth area: 12 mm²
1.4	Material / Resin	Plate / Foil bottom: CO (Cycloolefin), free of heavy metal Lid: PS (Polystyrene), free of heavy metal
1.5	Colour	Plate: black Lid: clear Foil bottom: clear
1.6	Sterilization	SAL 10^{-3}
1.7	Quality Control	Product-Control: testing of attributive and variable characteristics in accordance with the valid specification
1.8	Intended Use	General laboratory product for cell culture to be used by qualified personnel in a laboratory environment.
1.9	Other Information	For single use only

2.	**Features**	
2.1	Basic features	-
2.2	Temperature range	For application: + 4°C to +37°C
2.3	Autoclavability	No
2.4	Centrifugation, max. RCF	N/A
2.5	Chemical Resistance	See homepage: https://www.gbo.com/en_INT/know-how-services/download-center.html
2.6	Shelf life	2 years
2.7	Other Information	-

3.	**Packaging**	
3.1	Pieces / Bag	10
3.2	Pieces / Box	40
3.3	Lot-No.	B YY MM XXX (manufacturing facility, year, month, consecutive SAP-No.)
3.4	Other Information	Certificate of Quality to download

4.	**Other Information**
	-

Data Sheet subject to change without notice!

Prior Issue	**Drawn**	**Approved**	**Released**
Revision 05	Date 5 September 2022	Date 16 September 2022	Date 21 September 2022
Date 04.09.2019	Name S. Kaelberer	Name P. Wachter	Name A. Illig